

LED Cleanroom



PHILIPS

LED Cleanroom (CR652B)

USP

- ❖ Efficacy >90 lm/W
- ❖ > 40% energy saving Vs Conventional
- ❖ CRI > 80
- ❖ SDCM < 3.5
- ❖ Front Opening

Specifications

- CRCA housing with single piece CRCA frame
- Lumen Pack : 3300/ 5600 Lm
- System Power : 36W/60W
- Life : L70 , 50K Hrs
- IP 65 with Toughened Glass
- IP 54 with Clear Acrylic
- Suitable for front Opening Application



Technical Specification

Parameter	CR652B LED33S CR CW GT	CR652B LED33S CR NW CA	CR652B LED56S CR CW GT	CR652B LED56S CR NW CA
System Wattage	36W		60W	
Lumen Output	3300 lm		5600 lm	
System Efficacy	>90 lm/W			
Color Temperature	6500K	4000K	6500K	4000K
CRI	>80			
SDCM	<3.5			
PF	>0.9			
IP	IP 65	IP 54	IP 65	IP 54
Housing	White Powder Coated CRCA steel			
Frame	Single Piece white powder coated CRCA frame			
Mounting	Recessed			
Access for Maintenance	Bottom Opening			
Reflector	High reflective white power coated CRCA Steel			
Cover	Toughened Glass	Clear Acrylic	Toughened Glass	Clear Acrylic